

PRODUCT-DETAILS

## PMKHRMBRC3000A

## Redundancy Cable for Ctrl/Comm - 4 cm



General Information	
Product ID	PMKHRMBRC3000A
ABB Type Designation	Cable
Catalog Description	Redundancy Cable for Ctrl/Comm - 4 cm
Long Description	Redundancy Cable used for BRC300, BRC400, BRC410, NPM22, RIO22 or HPG800

Additional Information		
Medium Description	Redundancy Cable used for BRC300, BRC400, BRC410, NPM22, RIO22 or HPG800	
Product Type	Prefabricated_Cable	

## Ordering

HS Code

854442-- Insulated (including enamelled or anodised) wire, cable (including co-axial cable) and other insulated electric conductors, whether or not fitted with connectors; optical fibre cables, made up of individually sheathed fibres, whether or not assembled with electric conductors or fitted with connectors.- Other electric conductors, for a voltage not exceeding 1,000 V :-- Fitted with connectors

© 2025 ABB. All rights reserved.

2025/02/20

Subject to change without notice

85444290

Dimensions		
Product Net Depth / Length	10.16 mm	
Product Net Height	48.26 mm	
Product Net Width	25.4 mm	
Product Net Weight	0 kg	
Cable Diameter	0.01016 mm	

Environmental	
WEEE Category	Product Not in WEEE Scope
SCIP	No SVHC present Romania (RO)

## Categories

 $\mathsf{Control}\ \mathsf{Systems} \to \mathsf{Symphony}\ \mathsf{Harmony}\ \mathsf{INFI}\ 90 \to \mathsf{I/Os} \to \mathsf{Harmony}\ \mathsf{Block}\ \mathsf{I/O} \to \mathsf{P}-\mathsf{HA}-\mathsf{REP}-\mathsf{RFO} \to \mathsf{Prefabricated}\ \mathsf{Cables}$ 

